

Ultra V Pro STPXXXS - H48-Nkh+ 430-450W

96 (6 × 16)

21.5

(3)

-40 °C to +85 °C

1500 V DC (IEC)

35 A

(80 ± 5)%

Section A-A



Section B-B



Note:mm[inch]

	STP450S-H48-Nkh+		STP445S-H48-Nkh+		STP440S-H48-Nkh+		STP435S-H48-Nkh+		STP430S-H48-Nkh+	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
	450	344.1	445	340.2	440	336.4	435	332.6	430	328.8
	29.32	28	29.14	27.8	28.97	27.7	28.79	27.5	28.61	27.3
	15.35	12.29	15.27	12.23	15.19	12.16	15.11	12.1	15.03	12.04
	35.71	33.9	35.5	33.8	35.29	33.6	35.08	33.4	34.87	33.4
	16.01	12.91	15.93	12.84	15.85	12.78	15.77	12.72	15.69	12.65
(%)	22.5		22.3		22.0		21.8		21.8	

ST² 1.5;NMO² 1

5%	15%	25%
472.5	517.5	562.5
29.3	29.3	29.4
16.12	17.65	19.19
35.7	35.7	35.8
16.81	18.41	20.01
23.7	25.9	28.2

42 ± 2 °C

